
mac-attrs-docker

Aug 01, 2021

Contents:

1	Introduction	1
2	Installing mac-attrs-docker	3
3	Starting mac-attrs-docker	5
4	Using mac-attrs-docker	7
5	Testing mac-attrs-docker	9

CHAPTER 1

Introduction

mac-attrs-docker combines the functionality of [macaddress](#) and [random-mac](#) into a web app that evaluates the attributes of media access control (MAC) addresses.

CHAPTER 2

Installing mac-attrs-docker

mac-attrs-docker is available on GitHub at <https://github.com/critical-path/mac-attrs-docker>. It is the Docker version of `mac-attrs`.

To install it, run the following command from your shell.

```
[user@host ~]$ git clone git@github.com:critical-path/mac-attrs-docker.git
```


CHAPTER 3

Starting mac-attrs-docker

To start mac-attrs-docker for the first time, run the following command from your shell. This will build a Docker container from scratch.

```
[user@host mac-attrs-docker]$ docker-compose up --build
```

To restart it later, run the following command from your shell. This will preserve your progress.

```
[user@host mac-attrs-docker]$ docker-compose up
```


CHAPTER 4

Using mac-attrs-docker

Using mac-attrs-docker is easy!

First, point your browser to any of the following URLs.

- <http://localhost:8080/>
- <http://localhost:8080/home>
- <http://localhost:8080/home.html>
- <http://localhost:8080/index>
- <http://localhost:8080/index.html>
- <http://localhost:8080/mac-attrs>
- <http://localhost:8080/mac-attrs.html>

Second, type a MAC address.

Third, click on the `submit` button.

Fourth, view the results.

CHAPTER 5

Testing mac-attrs-docker

To conduct testing, run the following command from your shell.

```
[user@host mac-attrs-docker]$ docker-compose exec mac-attrs pytest --disable-warnings_  
↪ --cov --cov-report=term-missing
```